McEWEN



Shown: 60" model in Deep bronze anodized and Clear glass.

#### MODEL NUMBER

4620

## DESCRIPTION

Anodized aluminum frame with cut glass and polished aluminum reflectors. Cable Suspension.

#### FINISH

Deep bronze anodized or Silver anodized.

## KILN FORMED GLASS

Clear, Opal white, Pale gold or Sand.

DIMENSIONS 4620.36	MIN OAL	NET WT
6"W x 6"H x 36"L	10" Min. OAL	15 lbs.
4620.48 6"W x 6"H x 48"L	10" Min. OAL	20 lbs.
4620.60 6"W x 6"H x 60"L	10" Min. OAL	25 lbs.
4620.72 6"W x 6"H x 72"L	10" Min. OAL	30 lbs.

## CEILING PLATE

4.5"Ø x .25"D

#### **VOLTAGE / LAMP TYPE**

Integrated LED, 24V, 97 CRI Ra / 94 CRI R9 / 94 TM30 Rf / 102 TM30 Rg. 30,000 hr.

Clear & Sand: 2,400°K Opal white & Pale gold: 2,700°K

120V to 24V dimmable driver included. Must be located in remote cubby / crawl space. Recommend magnetic low voltage dimmer (Lutron SLV-600P or similar).

4620.36 40W, 2,400°K/3,240 lumens, 2,700°K, 3.384 lumens.

4620.48 54W, 2,400°K/4,293 lumens, 2,700°K, 4,484 lumens.

4620.60 74W, 2,400°K/5,937 lumens, 2,700°K, 6,200 lumens.

4620.72 80W, 2,400°K/6,480 lumens, 2,700°K, 6,768 lumens.

CA Title 24-JA8-2016

## PLEASE SPECIFY

Size, finish, glass color & OAL (net price includes cable for an OAL of up to 48"). Refer to price book for additional cable length. OAL can be adjusted in the field at installation.

# NOTE

J-box is located off-center on 36", 48" and 60" models.

## A620.36: 12" C to C
## 4620.48: 24" C to C
## 4620.60: 30" C to C
## 4620.60: 30" C to C
## 36", 48" or 60" Models



