



SKYLON-SURFACE 24"

ANTIQUE BRUSHED BRASS
STANDARD FIXED MOUNTS
TUBE WIRING



SKYLON-SURFACE 16"

BRUSHED NICKEL
ANTIQUE MOUNTING

SKYLON SURFACE

SKYLON-SURFACE

Molten glass, cast into delicate ribbons of flowing refraction, is edge-lit by a ring of LED. Bubbles and flow lines are completely unique to each casting and may vary significantly.

AVAILABLE SIZE/WEIGHT:

Heights may vary by 2"

16" Diameter x ~8" Tall, Approx 15lb

24" Diameter x ~9" Tall, Approx 21lb (shown)

30" Diameter x ~10" Tall, Approx 30lb

36" Diameter x ~11" Tall, Approx 40lb

45" Diameter x ~10" Tall, Approx 55lb

FINISHES:

Antique Brushed Brass / Black Brass / Brushed Brass / Brushed Nickel

ELECTRICAL:

2700K 95+ CRI LED, Dimmable Drivers (ELV) 120V Input

16": 32W 1000 Lumen

24": 55W 1900 Lumen

30": 75W 2600 Lumen

36": 80W 2700 Lumen

45": 100W 2900 Lumen

MOUNTING/CANOPIES:

Surface Skylon glass mounts directly to the ceiling.

- "Adjustable Wire Mounts" completely adjustable wire rope suspensions. Minimum 3" gap to ceiling. Most common.
- "Fixed Mounts": holds the skylon ~2" or greater specified length away from ceiling.

ELECTRICAL:

To connect power from the driver to the LEDs inside the glass ring, there are a few options. (specify one)

- "Concealed Wiring" Run the power from a canopy or a remote box in low volt wires behind the ceiling, right above the hanging support. Most common.
- "Tube Wiring" Connect the power through little tubes on the surface ceiling, for concrete/solid ceilings.
- Remote drivers allow class 2 wiring to connect to mounting points without any visible canopy.

Canopy Sizes:

16 & 24" Skylon Surface: 5" x 2" Canopy

30", 36", 45" Skylon Surface: 8.5" x 2.5" Canopy



SKYLON-SURFACE 45"

ANTIQUE BRUSHED BRASS / ADJUSTABLE MOUNTS / CONCEALED WIRING



SKYLON-SURFACE 24"

ANTIQUE BRUSHED BRASS / FIXED MOUNTS / TUBE WIRING

SKYLON-SURFACE 16"
NICKEL / ADJUSTABLE MOUNTS / CONCEALED WIRING

WIRING BETWEEN MOUNTING POINT IS CONCEALED BEHIND CEILING

CABLE GRIPPERS ALLOW ADJUSTABLE HEIGHT ON CABLE



SKYLON-SURFACE 30"
NICKEL / FIXED 3\"/>

WIRING RUNS INSIDE THE TUBES-FOR DIFFICULT CEILINGS

DROP IS FIXED BY THESE SOLID BRACKETS

