



Iwall Sconce

MODEL # 10138, 10139, 10140

Iwall has a glass fluted diffuser. It is mounted on the wall with rectangular backplates or no backplates on mirror mounting for 'floating' mirror effect. Designed by Doyle Crosby.

MATERIALS

Brass and glass

FINISHES

Polished Nickel or Satin Nickel

LAMPING

Iwall 2' (10138):

One, F14WT5/Mini Bi-pin, Voltage 120v or 277v (non-dimming)

Iwall 3' (10139):

One, F21WT5/Mini Bi-pin, Voltage 120v or 277v (non-dimming)

Iwall 4' (10140):

One, F28WT5/Mini Bi-pin, Voltage 120v or 277v (non-dimming)

DIMENSIONS

WEIGHT

Iwall 2' (10138):

W 3.625" x H 26.75" x D 3.75"
(92 mm x 679 mm x 95 mm)

8 lbs.
3.6 kg

Iwall 3' (10139):

W 3.625" x H 38.50" x D 3.75"
(92 mm x 978 mm x 95 mm)

9 lbs.
4.1 kg

Iwall 4' (10140):

W 3.625" x H 50.5" x D 3.75"
(92 mm x 1280 mm x 95 mm)

10 lbs
4.5 kg

NOTES

- Iwall 2' Backplates:
3.625" W x 4.5" H x 0.25" (92 x 114 x 6 mm)
- Iwall 3' Backplates:
3.625" W x 4.5" H x 0.25" (92 x 114 x 6 mm)
- Iwall 4' Backplates:
3.625" W x 4.5" H x 0.25" (92 x 114 x 6 mm)
- Center of outlet box to top of fixture: 2.25" (57 mm)
- ADA compliant at any mounting height
- UL listed (or equivalent) for damp locations
- Diffuser: clear, fluted glass with white spun filter
- Partially obscured 0.25" polished nickel wire way
- Horizontal or vertical mounting.
- Must mount to a mud-ring or switch-box
- Optional: mirror mount modification available (no backplates)
- Photometric report and ies file available
- Patent Design: D550,885.

